

Datasheet 2024.6

Patch panel, Category 6A, 24xRJ45/s, black, keystones included





Features

- 24 keystone jacks KEJ-CEA-S-10G included
- designed for 19" cabinets
- integrated cable management
- cable ties for gripping (24 pcs)
- set of M6 screws and captive nuts (4 pcs)
- grounding screw and washer (1 pc)

Application

- primary (Campus), secondary (Riser), tertiary (Horizontal)
- IEEE 802.3: 10BASE-T; 100BASE-T; 1000BASE-T; 10GBASE-T
- IEEE 802.5: 16 MB; ISDN; FDDI; ATM
- high bandwidth digital applications with low BER
- multimedia transmissions like digital and analog video and voice



Construction

| Height | | 1U (44,5 mm) |
|------------------------------------|------------------|--|
| Width | | 19" (482,6 mm) |
| Depth (including cable management) | | 152 mm |
| Material | front face | steel |
| Material | cable management | nickel-plated steel, corrosion-resistant |
| Color | | black RAL 9005 |
| Surface | | structured, matt |
| | | |



Keystone jack KEJ-CEA-S-10G mechanical properties

Note: for detailed information see datasheet for keystone jack KEJ-CEA-S-10G

| Suitable for installing on cables | with solid wires | from 0,51 to 0,64 mm (from AWG 24 to AWG 22) |
|-----------------------------------|---|--|
| Insertion / extraction cycles | min. 750 | |
| Temperature range | installation | -10 °C to +60 °C |
| | operational | -40 °C to +70 °C |
| IDC retermination | min. 20 | |
| Contact pin material | phosphor-bronze alloy coated with 6 μ of gold | |





6.7.7.7.79 6.7.7.7.79 6.7.7.779