

# Pigtail LC/APC

**P/N: PIG09-LCA-020**

OS2 singlemode 9/125 μm (ITU-T G.652.D)

**OS2**  
singlemode


## mechanical properties

Connector LC/APC	singlemode OS2
Polishing	APC
Return loss	> 65 dB
Insertion loss	0,15 dB (typical)
Length	2 m
Sheath material	halogen-free secondary EASySTRIP protection of 900 μm
Ferrule material	ceramic (zirconia)
Ferrule diameter	1,25 mm
Temperature range	-20 °C to +60 °C
Outer diameter	900±5 μm
Bending radius (static)	10 x 0,9 mm
Attenuation @ 850 / 1300 nm (dB/km)	-
Attenuation @ 1310 / 1383 / 1550 nm (dB/km)	≤ 0,4 / ≤ 0,4 / ≤ 0,4
Bandwidth 850 / 1300 nm (MHz.km)	-

## related products

<b>P/N: RAB-FO-X37-SL</b>	Sliding patch panel for 24 x SC-SC, LC-LC Duplex or E2000-E2000 adapters
<b>P/N: KE-LCDA-SM</b>	LC/APC-LC/APC adaptor
<b>P/N: RAB-FO-X04</b>	Splice cassette for 16 splices
<b>P/N: F11002</b>	Splice protection